

1280 X 800

1 Megapixel Cube IP Camera

Cube Series

- Built-in PIR Sensor and Illumination LED
- Built-in MIC and Speaker
- Built-in Micro SD memory card slot
- MPEG-4, MJPEG and H.264 Triple Codec Compression
- 802.11b/g/n Wireless connectivity (WGP-100-CB / WGE-100-CB)
- WPS supported for easy wireless network setup(WGP-100-CB / WGE-100-CB)



Cube Series

Product Name

1 Megapixel Cube IP Camera

Model Number

GP-100-CB

Wired Interface, 2-way audio, PIR, Illumination LED

WGP-100-CB

Wired and Wireless Interface, 2-way audio, PIR, Illumination LED

GE-100-CB

Wired Interface, 1-way audio

WGE-100-CB

Wired and Wireless Interface, 1-way audio

Hardware System

CPU : 500 MHz

Flash : 16M

RAM : 64M DDR

Image Sensor

GP-100-CB / WGP-100-CB

0 Lux (with LED), 1 Lux (without LED)

GE-100-CB / WGE-100-CB

1 Lux

Minimum Illumination

0 Lux (with LED), 1.5 Lux (without LED).

Lens

Lens Type : Board Lens

f = 3.6 mm, F 2.3

Video

Auto Exposure Control / Auto White Balance /

Auto Gain Control

Image Compression Format :

H.264 / MPEG4 / MJPEG

Max Image Resolution

-1280x800

Frame Rate @ Max. Resolution

H.264: 15 fps

MPEG4: 15 fps

MJPEG: 15 fps

Audio

GP-100-CB / WGP-100-CB

2-way audio / Built-in MIC / Built-in Speaker

GE-100-CB / WGE-100-CB

1-way audio / Built-in MIC

Communication

Ethernet : One 10 / 100 Mbps RJ-45

WiFi : 802.11 b/g/n (**WGP-100-CB / WGE-100-CB**)

Supported Protocols : TCP/IP, UDP, ICMP, DHCP,

NTP, DNS, DDNS, SMTP, FTP, HTTP, Samba,

PPPoE, UPnp, Bonjour, RTP, RTSP, RTCP

Interface & Buttons

GP-100-CB

Micro SD / SDHC card slot / DC Power Connector /

Ethernet Cable Connector / Privacy Button /

Reset Button / Microphone / PIR sensor / Speaker /

Illumination LED

WGP-100-CB

Micro SD / SDHC card slot / DC Power Connector /

Ethernet Cable Connector / Privacy Button /

WPS Button / Reset Button / Microphone /

PIR sensor / Speaker / Illumination LED

GE-100-CB

DC Power Connector / Ethernet Cable Connector /

Reset Button / Microphone

WGE-100-CB

DC Power Connector / Ethernet Cable Connector /

WPS Button / Reset Button / Microphone

LEDs

WGP-100-CB / WGE-100-CB

Power / Connection / Internet / WPS / Privacy

GP-100-CB / GE-100-CB

Power / Connection / Internet / Firmware Upgrade /

Privacy

Power Input

DC12V / 1A (Power Supply)

Environment

Operating Temperature : 0°C ~ 50°C (32°F~122°F)

Operating Humidity : 10% ~ 80%

Dimension

33 (L) X 69 (W) X 103 (H) mm

Weight

GP-100-CB

103 g

WGP-100-CB

108 g

GE-100-CB

97 g

WGE-100-CB

102 g